

SHEET 5- SECTION SHOWING GEOLOGY AND TUNNELING CONDITIONS


BY  
R. F. YERKES, J. M. McMANUS AND ERIK LAYMAN

MAPS AND SECTIONS OF THE LOS ANGELES CITY OIL FIELD

BY  
R. E. CROWDER  
(1961)

GEOLOGIC ASPECTS OF TUNNELING IN THE LOS ANGELES AREA, CALIFORNIA

BY  
R. F. YERKES, J. C. TINSLEY, AND K. M. WILLIAMS  
1977



EXPLANATION  
Geologic units and tunneling conditions

Approximate tunneling conditions for a given geologic unit may be inferred from its position relative to the water table and reference to the table:

Symbol	Geologic Unit	Lithology	Approximate Penetration Resistance, 50 ft. subsurface (BPF <sup>1/2</sup> )	Inferred Tunneling Conditions <sup>2</sup>	
				Dry	Wet
<u>SURFICIAL DEPOSITS</u>					
af	Artificial fill	Silt, sand, gravel; admixed clay, asphalt, concrete		4-5 10*	6 10*
Qal	Alluvium	Silty to sandy gravel, locally with cobbles and boulders; locally petroliiferous; locally slightly consolidated	>40	4-5 10*	6 10*
Qalo, Old alluvium		Slightly consolidated gravel; clayey, with cobbles and boulders; commonly unconsolidated	>40	3-5 10*	5-6 10*
Qsp	San Pedro Formation of Thomas, Landry, and Turney (1961)	Semiconsolidated sand and fine gravel (<1/4 in.), interbedded silt sand, sandy silt, and clay		3-5	5-6 10*
<u>BEDROCK UNITS</u>					
Tfsl	Siltstone, Fernando Formation of Lamar (1970)	Soft, massive siltstone, local layers hard pebble (<1/4 in.) conglomerate; rare hard calcareous beds; locally petroliiferous	>22	3-4	4-5
<u>Puente Formation of Lamar (1970):</u>					
Tpds	Diatomaceous shale and diatomite	Soft, punky, blocky weathering, thinly laminated; rare beds soft friable sandstone and massive, hard limestone	damp: >38 dry: 24-38	3-4	4-5
Tpsl	Siltstone and very fine-grained sandstone	Poorly cemented, closely jointed, blocky; beds <5 ft. thick; layers shale chips, pebbles, and slabs of hard limestone; few beds <3 in. thick of hard limestone	>30	3-4	4-5
Tpss	Sandstone	Hard and well cemented (dolomite?) with very hard calcareous concretions; beds <10 ft. thick; local thin beds of shale, fragments shale and siltstone		3-4	4-5
Tpum	Undivided sandstone and shale	Hard and well cemented to poorly cemented sandstone; very hard, fissile, siliceous shale and blocky siltstone; some beds <3 ft. hard limestone; also some conglomerate of angular fragments <2 in. of shale and quartz		3-4	4-5
<u>Topanga Formation of Lamar (1970):</u>					
Ttsl	Siltstone, sandstone and shale	Commonly very hard, closely jointed, blocky; shale siliceous, hard rhythmically bedded <2 in.; sandstone beds <3 ft.; limestone beds <2 ft.; some very hard buff and tuffaceous sandstone		3-4	4-5
Ttgc	Pebbly sandstone and conglomerate	Commonly hard, well cemented (calcareous?) in beds <4 ft.; pebbles hard rock average 2 in. but contains boulders to 3 ft.		3-5	4-6
<u>BASEMENT ROCKS</u>					
fgd	Feliz Granodiorite of Lamar (1970)	Deeply weathered, soft, crumbly		4-6	6-8

Lines and symbols

Contact between geologic units  
Solid, well located; long dash, approximately located; short dash, location inferred; queried where doubtful

Dip of strata  
Horizontal  
Apparent  
Vertical

Long dash, approximately located; short dash, location inferred; queried where doubtful

Approximate location of water table  
Number shows year of measurement. Solid triangle, location of 1974 measurements; open triangle, location of pre-1974 measurement.  
pw, perched water table; queried where inferred scale distortion); number gives true dip

Special symbols

Identifying number  
(Sheet 3, table 1)

Surface casing

Well or boring

Significant conditions  
b, boulders (>10 in. in diameter)  
c, cobbles (2 1/2 - 10 in.)  
h, H<sub>2</sub>S odor (1962)  
p, petroliiferous  
v, very hard drilling (rotary equipment)

1/2-in. split spoon, 140-lb. hammer, 30-in. drop; units tested along line of section A-D; see fig. 3 for complete results of tests.

Summary of soft-ground tunneling conditions used (see table 2 for definitions):  
2 - Hard stratified or schistose  
3 - Very firm ground  
4 - Firm ground; may ravel when wet  
5 - Very blocky or sandy; may ravel when wet  
6 - Unconsolidated or crushed materials; may run or flow when wet  
10 - Bouldery (hard rock fragments >10 in. in long diameter)

\*If bouldery